

Working range:	< 3" *
Clamping force:	8 kN (8 bar)

A tool for two functions: The new UNE 115 is the high-performance tool for production and the workshop. This equipment now permits fittings up to 3" to be inserted or extracted. Due to its innovative rapid tool sled, the insertion of 90 degree, 45 degree or straight fittings without changing tools is now simple and quick.

Ergonomic

- Freely positional foot pedal for clamping hose saves time and increases productivity
- Lifting eyes for easy positioning of the machine

Simple to use

- Universal hose clamping jaws for all hose diameters without the need for changeover eliminates lengthy setup times
- Axially adjustable clamping unit for all diameters prevents kinking of thin hoses and for efficient operation
- Individual clamping force adjustment for damage-free clamping avoiding scrap
- Zero maintenance and wear contributes to cost savings
- Rapid sled for inserting curved and straight fittings without time-consuming exchange of fork sets saves time

Safety compliant

- Moving components have safety guarding
- CE-compliant, robust UNIFLEX quality

CARACTERISTIQUES TECHNIQUES :

Modell:	UNE 115
Working range	< 3" *
Hose max. outside	Ø 120 mm
Compressed air connection	8 bar
Insertion force	8 kN (8 bar)
Clamping force	8 kN (8 bar)
Control	Manual (Footpedal)
L x W x H (mm)	625 x 1185 x 320
Poids	100 Kg
Pneum. Air Supply	7 bar / 100 psi Kg



Adresse lot 12 hectares rue « B » N 17 BBA Email : contact@flexibordj.com Site www.flexibordj@live.com MOB
0770959812/0770281512 TEL/FAX 035723795